

Six inch Pump Comparison

Make sure you are comparing apples to apples when discussing equipment

Standard Self Priming Pump



Godwin CD150M Silenced



Godwin CD150M



Syke GP150M Silenced



Sykes GP150MC



Sykes WP150/200



Max Volume, gpm	1300	1700	1700	2250	2250	1700
Max Head, ft	100	160	160	165	165	160
Run Dry	No	Yes	Yes	Yes	Yes	Yes
Seal Type	Silicon Carbide Mechanical	Oil Cooled Mechanical	Oil Cooled Mechanical	GFO Braded Packing	GFO Braded Packing	GFO Braded Packing
Priming	Manual	Automatic	Automatic	Automatic	Automatic	Automatic
Max Suction Lift, ft	25	28	28	30	30	30
Vacuum CFM	10	12	12	74	74	74
Backflush Suction	No	No	No	Yes	Yes	Yes
Auto Float System	No	Optional	Optional	Standard	Optional	Optional
Fuel Capacity, gal	24	60	60	125	125	60
Noise Rating decibels, 30 ft	90	69	115	69	100	90
Solids Handling, inches	2	3	3	3	3	3
Standard Dewatering	Yes	Yes	Yes	Yes	Yes	Yes
Sewer Bypass	No	Yes	Yes	Yes	Yes	Yes
Well Point Dewatering	No	No	No	Yes	Yes	Yes

What do some of the numbers mean?

The Sykes GP150M produces 20% more volume than the Godwin CD150M

The Sykes primes at least 4 times faster than the Godwin

The Sykes has twice the fuel capacity

Internal Use Only

All information from manufacturers literature