

SULLAIR® TSR-20

VARIABLE SPEED DRIVE INSTRUMENT QUALITY AIR COMPRESSOR

RENTAL READY PACKAGE

- Aftercooled to 20° F above ambient final discharge air temperature
- After-filtered available upon request to .01 PPM Oil Vapor
- Automatic Condensate Drains
- Auto Start and Sequencing Capability
- Customer Hook-up (Twist Lock Connectors)
- Phase Rotation Indicator Light
- 110% Environmentally Self Contained
- Heavy Duty Rental Package
- 78 dbA @ 3'
- Energy Efficiency Rating 96.20%
- Air Discharge Outlet Size 2"



SPECIFICATIONS

HP	100 PSI	125 PSI	150 PSI	175 PSI	START AMPS	FULL LOAD AMPS	DIMENSIONS	
100	555 CFM	485 CFM	430 CFM	380 CFM	153	153	L	13'
125	685 CFM	615 CFM	555 CFM	495 CFM	186	186	W	6'2"
150	815 CFM	740 CFM	680 CFM	610 CFM	220	220	H	7'2"
200	970 CFM	900 CFM	845 CFM	775 CFM	286	286	WT	11,600

4/07

All Amp readings based on 460 volt. All figures above are approximate.

PETERSON
POWER SYSTEMS



www.petersonpower.com

California: (800) 963-6446 Oregon: (866) 228-3447

2828 Teagarden Street, San Leandro, CA 94577
1626 30th Street, Springfield, OR 97478