

## Model PY -5EHSS

Model PY-5EHSS-CU Condensing Unit  
Model PY-5EHSS-AH Air Handling Unit  
ARI System Capacity: 61,500 BTU, 1,930 CFM



LEFT SIDE



FRONT

Model PY-5EHSS-CU Condensing Unit  
Dimensions: Overall Length 52.5", Width 32.5", Height 41"  
Approximate Weight: 420 Lbs.



RIGHT SIDE



FRONT



LEFT SIDE



REAR

Model PY-5 EHSS-AH Air Handler  
Dimensions: Overall Length 26", Width 31.5", Height 80"  
Approximate Weight: 335 Lbs.



## Model PY -5EHSS

Model PY-5EHSS-CU Condensing Unit  
Model PY-5EHSS-AH Air Handling Unit  
ARI System Capacity: 61,500 BTU, 1,930 CFM

### STANDARD FEATURES - CONDENSING UNIT (CU)

- York International system components.
- Fully welded aluminum transport frame.
- Full fork lift tubes.
- Condenser coil guards with lift off hinges.
- NEMA 3R control center with all UL listed components.
- Lockable main power disconnect.
- Internal component circuit breakers.
- Ultra quiet operation.
- Refrigerant quick-disconnect fittings, EPA approved.
- Swivel casters.

### STANDARD FEATURES - AIR HANDLING UNIT (AHU)

- Rugged cabinet construction.
- Powder coated access panels with stainless steel latches and lift off hinges.
- Automatic condensate pump out system.
- Swivel casters with integral leveling pads.
- Programmable heat / cool thermostat, unit or remote mounted, NEMA 4.
- Main power breaker.
- Electric heat, 15/20 kW (operates independent of Condensing Unit).
- Heater has independent power supply.
- Smoke detector for emergency shut down.
- Refrigerant quick-disconnect fittings.
- Designed to fit through a 36" door.
- Ultra quiet operation (55 dBA).
- Configurable discharge grills, 3 sides and top.

### SYSTEM ELECTRICAL REQUIREMENTS

- System Ampacity (Cooling and Convenience Outlets Only): 75.0 Amps, 208-230/60/3  
Condensing Unit : 45.0 Amps, Convenience Outlets: 20.0 Amps  
Air Handling Unit Fans: 5.0 Amps each, 10.0 Amps total
- AHU Electric Heat and Fan Ampacity: 15 KW, 97.0 Amps, 208/60/1  
20 KW, 110.0 Amps, 230-240/60/1

