

Sullair DE-18.

When the only acceptable standard is 100% oil-free air.*

Rugged

- Oil field skid
- Four point lift
- Fork lift pockets
- Stainless steel piping
- Heavy duty enclosure
- 115% fluid containment

Versatile

- Air-cooled package
- Suitable for outdoors
- Cold weather protection
- Auxiliary heaters
- Self contained package
- Noise attenuated enclosure
- Low engine emissions
- Sequencing capabilities

User friendly

- Electronic fuel system
- Integrated control systems
- Fully automated controls
- External user connections
- Remote fueling connections
- Lockable doors



The only package designed
by the Rental Industry for the Rental Industry.



SULLAIR
OIL-FREE PRODUCTS

* Compressors are not designed, intended or approved for breathing air.

Sullair DE-18

Sullair, Oil-Free, Engine-Driven, Rental Package. When the only acceptable standard is 100% oil-free air.*

Compressor data:

- Type: two-stage, rotary, oil-free, screw compressor
- Rated capacity: 1,550 cfm at 125 psig—727 L/S at 8.5 bar
- Pressure range: 75 to 135 psig (150 psig available)—5.2 to 9.3 bar (10 bar available)
- Discharge connection: 4 inch, NPT—102 mm
- Discharge air temperature: 15 to 20 degree F “approach”—8 to 11 degree C

Engine data:

- Size: Caterpillar C-15 ATAAC Tier 3, 540 HP (403 KW), 928 cu. in. displacement (15.2 L)
- Type: In-line, 6 cylinder, 4-stroke, turbo charged diesel, with electronic fuel system
- Speed: 1,400 to 1,840 rpm
- Fuel capacity: 245 gallons—927 L
- Emissions: Tier level 3

Package data:

- Maximum elevation: 12,000 ft, with de-ration—3658 m, with de-ration
- Power requirement, for the cold weather package: 50 amps (80 max) amps, 120v/1 ph/60Hz
- Dimensions (l x w x h): 228 x 88 x 98 inches—5791 x 2235 x 2489 mm
- Package dry weight: 23,200 lbs. (no fuel)—10, 524 kg (no fuel)
Package wet weight: 25,000 lbs (full fuel tank)—11,340 kg (full fuel tank)
Optional wheel kit: add +3,000 lbs—+1,361 kg
- Noise level: 76 dBA at 7 meters

Air-End Warranty:

- 2 year standard warranty. 5 year or 10,000 hour warranty when continuously serviced at the recommended intervals with Sullair AWF Compressor Fluid and filters.

Options:

- Caster-type steerable wheel kit for maneuvering in yard
- Special paint



* Compressors are not designed, intended or approved for breathing air.



www.sullair.com

SULLAIR CORPORATION, 3700 E. Michigan Blvd., Michigan City, IN 46360 Telephone: 1-219-879-5451

SSL-15004C Specifications subject to change without notice. © Copyright 2006 Sullair Corporation. All rights reserved. EA/06/07/5