

TEMPERATURE CONTROL EQUIPMENT

PACKAGED COOLING/HEATING AIR CONDITIONER MODEL PY-5GP NOMINAL 5 TONS

STANDARD FEATURES

York single packaged air conditioning unit.
Available in 208-230/60/3 or 460/60/3 volts.
Rugged welded steel transport frame.
Full fork lift tubes and lifting eyes.
Stackable for transport or storage.
High efficiency scroll compressor
Energy Efficiency Ratio of 10.0 (EER).
Condenser coil guards.
Ultra quiet operation.
Direct drive blower motor, 3/4 HP.

Pleated media filters, 30% efficient.
Square to round (20") duct adapters.
Cam-lock main power connections.
Lockable main power disconnect.
Internally mounted circuit breakers.
Propane or natural gas heat with electronic
spark ignition.
Phase rotation protection.

UNIT CAPACITY

Cooling Capacity at ARI Conditions: 58,500 Btu.
Heating Capacity: 100,000 Btu Input, 79,000 Btu Output.
Nominal Blower Capacity: 2,000 CFM.

ELECTRICAL REQUIREMENTS

Total Unit Ampacity: 34.0 Amps, 208-230/60/3
18.0 Amps, 460/60/3

**Model PY-5GP
Packaged Air Conditioner**



OVERALL LENGTH 95", WIDTH 48.5", HEIGHT 47", APPROXIMATE WEIGHT 975 LBS.

