

100 Amp Load Center



Image shown may not reflect actual package.

100 Amp Load Center

Specifications	
Number of Spaces	6
System Voltage	120 / 240VAC
Number of Tandem Circuit Breakers	6
Phase	1 Ph
NEMA Degree of Protection	NEMA 3R Outdoor
Electrical Connection	Lugs
Wiring Configuration	3-Wire
Material	Tin Plated Aluminum Busbar
Enclosure Material	Welded Galvanized Steel
Cover Finish	Gray Baked Enamel
Product Certifications	UL E-6294
Gauge	AWG 8...AWG 1 (Aluminium / Copper)

Dimensions and Specifications	
Height / Width / Depth	321 mm / 226 mm / 127 mm
GFCI	16A (120V)
Battery Charger	6A (120V)
Jacket Water Heater	11.25A (240V)
Alternator Heater	1.04A (240V)
Total Load	34.29A Max

L1	
GFCI	16A (120V)
Jacket Water Heater	11.25A (240V)
Alternator Heater	1.04A (240V)
Total Load	28.29A Max

L2	
Battery Charger	6A (120V)
Jacket Water Heater	11.25A (240V)
Alternator Heater	1.04A (240V)
Total Load	18.29A Max

www.cat.com/electricpower

©2020 Caterpillar
All rights reserved.

Information contained in this publication may be considered confidential. Discretion is recommended when distributing. Materials and specifications are subject to change without notice.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.