

SULLAIR® LSR-16

VARIABLE SPEED DRIVE INSTRUMENT QUALITY AIR COMPRESSOR

RENTAL READY PACKAGE

- Aftercooled to 20° F above ambient final discharge air temperature
- After-filtered available upon request to .01 PPM Oil Vapor
- Automatic Condensate Drains
- Auto Start and Sequencing Capability
- Customer Hook-up (Twist Lock Connectors)
- Phase Rotation Indicator Light
- 110% Environmentally Self Contained
- Heavy Duty Rental Package
- 78 dbA @ 3'
- Energy Efficiency Rating 96.20%
- Air Discharge Outlet Size 1 1/2"



SPECIFICATIONS

HP	100 PSI	125 PSI	150 PSI	175 PSI	START AMPS	FULL LOAD AMPS	DIMENSIONS	
40	175 CFM	149 CFM			63	63	L	8'4"
50	230 CFM	197 CFM	174 CFM	150 CFM	77	77	W	4'1"
60	280 CFM	245 CFM	215 CFM	188 CFM	89	89	H	7'1"
75	351 CFM	310 CFM	278 CFM	255 CFM	111	111	WT	5,500

4/07

All Amp readings based on 460 volt. All figures above are approximate.

PETERSON
POWER SYSTEMS

CAT®

www.petersonpower.com

California: (800) 963-6446 Oregon: (866) 228-3447

2828 Teagarden Street, San Leandro, CA 94577
1626 30th Street, Springfield, OR 97478